



## FD810R

Auto aligning reflective beam detector 50 - 100m

### General

The FD810R consist of an infrared transmitter and receiver in one compact housing, and a ground level controller, which also doubles as a user interface for configuration and maintenance. The infrared signal from the detector is reflected by a prism and analyzed for smoke presence. It is particularly designed to be used where point smoke detectors are not applicable due to height or inaccessibility. The FD810R also features a motorized head, which allow for auto realignment in cases where gradual building shift occurs. The unit has relay outputs for alarm and fault and fits as such all types of fire panels



### Installer friendly

Getting the system operational is simplified by a number of groundbreaking features that combine to make the FD810R the quickest and easiest detector of its type to install. Once the detector head is connected, using the Easifit First Fix system, an integral LASER, which is aligned along the optical path of the beam, can be activated. This allows the reflective prism to be sighted quickly and with confidence. Once the LASER has been used to coarsely align the beam, the AutOptimise beam alignment system takes over and automatically steers the beam into the optimum position.

### Flexibility

The system can be fully customised, according to the requirements of each installation. Both alarm thresholds (sensitivity) and time to Alarm/Fault can be set from the ground level System Controller. Additionally, the integrated accessory mount allows the use of a variety of standard fittings solve any specific installation issues.

### Standard Features

- EN54-12 Approved
- Building Shift Compensation
- 2-wire Interface from Detector to System Controller
- Laser Assisted Alignment
- Automatic Contamination Compensation
- Auto Alignment

# FD810R

Auto aligning reflective beam detector 50 - 100m

## Specifications

<b>Supply voltage</b>	14 -28 VDC
<b>Range</b>	50 - 100 m
<b>Lateral detection</b>	7.5 m
<b>Current consumption</b>	
low current mode	8 - 12 mA
high current mode	48 - 52 mA
<b>Output relay rating</b>	
Voltage	0.1 to 220 VDC
Current	0.1 to 500 mA
<b>Optical wave length</b>	850 nm
<b>Operating temperature</b>	-20°C to 55°C
<b>Dimensions detector</b>	
W x H x D	135 x 135 x 135 mm
Weight	500 g
<b>Dimensions controller</b>	
W x H x D	200 x 235 x 71 mm
Weight	900 g
<b>Dimensions reflector</b>	
W x H x D	100 x 100 x 9.5 mm
Weight	70 g
<b>IP rating</b>	IP54
<b>Colour</b>	Gray-black

## Ordering Information

Part No.	Description
FD810R	Auto aligning reflective beam detector 50 - 100m
FD805R	Auto aligning reflective beam detector 8 - 50m



[www.gesecurity.net](http://www.gesecurity.net)

As a company of innovation, GE Security reserves the right to change product specifications without notice. For the latest product specifications, visit GE Security online or contact your GE Security sales representative.

IPS-FD810R-2008-12-2 12:28:14 Released : 23.07.2008;